

Recommended Load & Inflation

Tire Size Designation	Pattern	PR	Use	Tire Load Limits at Various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load)																		
				psi	65	70	75	80	85	90	95	100	105	110	115	120	125	130				
				kg																		
17.5 215/75R17.5	GTR955	16	DUAL	kg								1650	1720	1790	1860	1910	1990	2060	2120(H)134			
				lbs							3645	3795	3945	4095	4220	4390	4540	4675(H)				
			SINGLE	kg										1750	1820	1900	1960	2040	2110	2180	2240(H)136	
				lbs										3860	4010	4180	4330	4500	4650	4805	4940(H)	
17.5 235/75R17.5	GTR955	16	DUAL	kg								2165	2235	2305	2375	2435	2505	2545	2575(H)141			
				lbs							4772	4926	5089	5235	5367	5521	5610	5675(H)				
			SINGLE	kg										2315	2385	2455	2525	2585	2655	2692	2725(H)143	
				lbs										5102	5257	5411	5565	5697	5852	5935	6005(H)	
19.5 225/70R19.5	GSR139, GDR339	14	DUAL	kg	1180	1230	1300	1360	1410	1470	1550(F)123	1580	1640	1700(G)126	1750	1800(H)128						
				lbs	2600	2720	2860	3000	3115	3245	3415(F)	3490	3615	3750(G)	3855	3970(H)						
			SINGLE	kg	1250	1310	1380	1450	1500	1570	1650(F)125	1690	1740	1800(G)128	1860	1900(H)130						
				lbs	2755	2895	3040	3195	3315	3450	3640(F)	3715	3845	3970(G)	4100	4190(H)						
19.5 245/70R19.5	GSR139, GDR339	16	DUAL	kg																		
				lbs	1320	1390	1460	1550	1590	1660	1750(F)127	1790	1850	1950(G)131	1970	2120(H)134						
			SINGLE	kg	2910	3070	3220	3415	3515	3655	3860(F)	3940	4075	4300(G)	4345	4675(H)						
				lbs	1400	1480	1550	1650	1700	1770	1850(F)129	1900	1970	2060(G)133	2095	2240(H)136						
22.5 11R22.5	GSR135FE, GDR335FE, GDR688, GDR750FE, GAM535	16	DUAL	kg		1990	2080	2160	2250	2360(F)138	2460	2560	2650(G)142	2680	2710	2725(H)143						
				lbs		4380	4580	4760	4950	5205(F)	5415	5625	5840(G)	5895	5950	6005(H)						
			SINGLE	kg		2050	2160	2260	2370	2500(F)140	2600	2700	2800(G)144	2870	2940	3000(H)146						
				lbs		4530	4770	4990	5220	5510(F)	5730	5950	6175(G)	6320	6465	6610(H)						
22.5 315/80R22.5	GAM535	22	DUAL	kg							2650	2750	2900	2970	3070	3150	3270	3940	4125(M)157			
				lbs							5840	6070	6395	6540	6770	6940	7210	8680	9090(M)			
			SINGLE	kg										2910	3030	3150	3260	3370	3450	3590	4330	4625(M)161
				lbs										6415	6670	6940	7190	7440	7610	7920	9545	10200(M)
22.5 295/75R22.5	GSR135FE, GDR335FE, GDR688, GDR750FE	16	DUAL	kg		1860	1950	2060	2130	2220	2300(F)137	2390	2470	2575(G)141	2630	2725(H)143						
				lbs		4095	4300	4540	4690	4885	5070(F)	5260	5440	5675(G)	5795	6005(H)						
			SINGLE	kg		2040	2140	2240	2340	2440	2500(F)140	2620	2710	2800(G)144	2890	3000(H)146						
				lbs		4500	4725	4940	5155	5370	5510(F)	5780	5980	6175(G)	6370	6610(H)						
22.5 255/70R22.5	GSR135FE, GDR335FE, GDR750FE	16	DUAL	kg	1550	1630	1710	1800	1860	1940	2000	2020	2090	2120(G)134	2230	2300(H)137						
				lbs	3415	3585	3765	3970	4110	4275	4410	4455	4610	4675(G)	4915	5070(H)						
			SINGLE	kg	1650	1730	1820	1900	1980	2060	2120	2220	2300	2360(G)138	2450	2500(H)140						
				lbs	3640	3815	4005	4190	4370	4550	4675	4895	5065	5205(G)	5400	5510(H)						
22.5 385/65R22.5	GAM876	18	DUAL	kg																		
				lbs																		
			SINGLE	kg		2880	3060	3150	3350	3470	3650	3740	3850	4000	4100	4250(J)158	4340	4500(L)160				
				lbs		6380	6720	6940	7350	7650	8050	8230	8510	8820	9050	9370(J)	9570	9920(L)				
22.5 425/65R22.5	GAM876	20	DUAL	kg																		
				lbs																		
			SINGLE	kg	3430	3430	3640	3750	3980	4130	4250	4440	4580	4750	4880	5150(L)165	5475	5800(M)169				
				lbs	7560	7590	7990	8270	8740	9100	9370	9790	10100	10500	10700	11400(L)	12100	12800(M)				
24.5 11R24.5	GSR135FE, GDR335FE, GDR688, GDR750FE, GAM535	14	DUAL	kg		2110	2210	2300	2390	2500(F)140	2580	2660	2725(G)143	2820	2910	3000(H)146						
				lbs		4660	4870	5070	5260	5510(F)	5675	5840	6005(G)	6205	6405	6610(H)						
			SINGLE	kg		2190	2300	2410	2520	2650(F)142	2770	2890	3000(G)146	3080	3160	3250(H)149						
				lbs		4820	5070	5310	5550	5840(F)	6095	6350	6610(G)	6790	6970	7160(H)						
24.5 285/75R24.5	GSR135FE, GDR335FE, GDR688	16	DUAL	kg			1970	2060	2150	2240	2360(F)138	2410	2490	2575(G)141	2660	2800(H)144						
				lbs			4340	4540	4740	4930	5205(F)	5310	5495	5675(G)	5860	6175(H)						
			SINGLE	kg			2160	2240	2360	2460	2575(F)141	2650	2740	2800(G)144	2920	3075(H)147						
				lbs			4770	4940	4940	5210	5675(F)	5835	6040	6175(G)	6440	6780(H)						