

Recommended Load & Inflation

	Tire Size Designation	Pattern	PR	Use	Tire Load Limits at Various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load)																
					psi	65	70	75	80	85	90	95	100	105	110	115	120	123	125	130	
17.5	215/75R17.5	GTR955	16	DUAL	kg			1450	1520	1590	1650	1720	1790	1860	1910	1990		2060			
					lbs			3196	3350	3504	3637	3791	3945	4099	4210	4386		4540	4675		
					SINGLE	kg			1570	1640	1710	1770	1840	1910	1980	2040	2110		2180		
						lbs			3460	3615	3769	3901	4055	4210	4364	4496	4650		4805	4940	
		235/75R17.5	GTR955	16	DUAL	kg			1965	2035	2105	2165	2235	2305	2375	2435	2505			2575(H)141	
						lbs			4331	4485	4639	4772	4926	5080	5235	5367	5521			5675(H)	
				SINGLE	kg			2115	2185	2255	2315	2385	2455	2525	2585	2655			2725(H)143		
					lbs			4661	4816	4970	5102	5257	5411	5565	5697	5852			6005(H)		
19.5	225/70R19.5	GSR139, GDR339	14	DUAL	kg	1170	1220	1290	1360	1430	1490	1560	1630	1700(G)126							
					lbs	2579	2689	2843	2997	3152	3284	3438	3593	3750(G)							
					SINGLE	kg	1270	1320	1390	1460	1530	1590	1660	1730	1800(G)128						
						lbs	2799	2909	3064	3218	3372	3504	3659	3813	3970(G)						
		245/70R19.5	GSR139, GDR339	16	DUAL	kg			1580	1650	1720	1780	1850	1920	1990	2050	2120(H)134				
						lbs			3482	3637	3791	3923	4077	4232	4386	4518	4675(H)				
				SINGLE	kg			1700	1770	1840	1900	1970	2040	2110	2170	2240(H)136					
					lbs			3747	3901	4055	4188	4342	4496	4650	4783	4940(H)					
22.5	11R22.5	GAM535	16	DUAL	kg			2185	2255	2325	2385	2455	2525	2595	2655	2725(H)143					
					lbs			4816	4970	5124	5257	5411	5565	5719	5852	6005(H)					
					SINGLE	kg			2460	2530	2600	2660	2730	2800	2870	2930	3000(H)146				
						lbs			5422	5576	5730	5863	6017	6171	6325	6458	6610(H)				
		11R22.5, 295/75R22.5	GSR135FE, GDR335FE, GDR688, GDR750FE	14	DUAL	kg	1860	1950	2060	2130	2220	2300(F)137	2390	2470	2575(G)141	2630	2725(H)143				
						lbs	4095	4300	4540	4690	4885	5070(F)	5260	5440	5675(G)	5795	6005(H)				
				SINGLE	kg	2040	2140	2240	2340	2440	2500(F)140	2620	2710	2800(G)144	2980	3000(H)146					
					lbs	4500	4725	4940	5155	5370	5510(F)	5780	5980	6175(G)	6370	6610(H)					
	255/70R22.5	GSR135FE, GDR335FE, GDR750FE	16	DUAL	kg			1760	1830	1900	1960	2030	2100	2170	2230	2300(H)137					
					lbs			3879	4033	4188	4320	4474	4628	4783	4915	5070(H)					
				SINGLE	kg			1960	2030	2100	2160	2230	2300	2370	2430	2500(H)140					
					lbs			4320	4474	4628	4761	4915	5069	5223	5356	5510(H)					
24.5	385/65R22.5	GAM876	16	DUAL	kg																
					lbs																
					SINGLE	kg	2880	3060	3150	3350	3470	3650	3740	3850	4000	4100	4180	4250			
						lbs	6348	6744	6943	7383	7648	8045	8243	8485	8816	9036	9213	9370			9920
		425/65R22.5	GAM876	16	DUAL	kg														2650 (H) 142	
						lbs															
				SINGLE	kg	3430	3640	3750	3980	4130	4250	4440	4580	4750	4880	5150(L)165				2800 (H) 144	
					lbs	7560	8023	8265	8772	9103	9367	9786	10094	10469	10756	11400(L)				6175 (H)	
24.5	11R24.5	GAM535	14	DUAL	kg			2460	2530	2600	2660	2730	2800	2870	2930	3000(H)146					
					lbs			5422	5576	5730	5863	6017	6171	6325	6458	6610(H)					
					SINGLE	kg			2710	2780	2850	2910	2980	3050	3120	3180	3250(H)149				
						lbs			5973	6127	6281	6414	6568	6722	6876	7009	7160(H)				
		11R24.5	GSR135FE, GDR335FE, GDR688, GDR750FE	16	DUAL	kg			2460	2530	2600	2660	2730	2800	2870	2930	3000(H)146				
						lbs			5422	5576	5730	5863	6017	6171	6325	6458	6610(H)				
				SINGLE	kg			2710	2780	2850	2910	2980	3050	3120	3180	3250(H)149					
					lbs			5973	6127	6281	6414	6568	6722	6876	7009	7160(H)					
	285/75R24.5	GSR135FE, GDR335FE, GDR688	16	DUAL	kg	1870	1970	2060	2150	2240	2360	2410	2490	2575(G)141							
					lbs	4121	4342	4540	4739	4937	5201	5312	5488	5675(G)			6175(H)				
				SINGLE	kg	2060	2160	2240	2360	2460	2575	2650	2740	2800(G)144							
					lbs	4540	4761	4937	5201	5422	5675	5841	6039	6175(G)			6780(H)				